

MJ-1.4 ST H
MJ-1.8 ST H
MJ-2.3 ST H
High pressure

For versatile crushing

MERICRUSHER WORKING ENVIRONMENTS

FOREST

- Crushing of leftovers
- Preparing of hauling lines
- Soil preparing for planting
- Maintenance of forest roads
- Bush clearing

CONSTRUCTION

- Clearing of building sites
- Crushing of stumps
- Ice crushing
- Clearing land before seeding and planting

AGRICULTURE

- Clearing of farm land
- Farm road maintenance

EQUIPMENT

FEATURES

- Bolt mounted counter blades
- Hardox liner (frame MJ-1.8 / 2.3)
- STD Rotor with cutters

OPTIONS

- Push bar (fixed)
- Guide plate (front fixed)
- Hardox liner (frame MJ-1.4)

Base machine demand

Compact loaders (skid steer)

Mounting SAE J2513

Hydraulic High pressure (case drain)

Power range 250-350bar 100-220 l/min
3600 /5100psi 26 /58gal/min

Lifting capacity Min 1400kg / 3800 lbs

Technical data:

Transmission Hydraulic

Hydraulic motor Hig pressure - piston motor

Final transmission Chain 2-row

Rotor diameter 400 mm 20 inch

Rotor width 1.4 / 1.8 / 2.3 1350 / 1750 / 2250mm 53 / 69 / 88 inch

Cutter qty. 1.4 / 1.8 / 2.3 60 / 76 / 96 (T25 rotor)

Working depth 200mm / 8 inch

Main dimensions:

Length 815 mm 32 inch

Width 1.4 / 1.8 / 2.3 1580 / 1980 / 2700 mm 62 / 78 / 106 inch

Height 790 mm 31 inch

Weight 1.4 / 1.8 / 2.3 540 / 650 / 900 kg 1450 / 1740 / 2400lbs

Weight, with options 1.4 / 1.8 / 2.3 750 / 950 / 1350kg 2000 / 2550 / 3600lbs



MERICRUSHER
 DIFFERENT FOR A REASON