

MERICRUSHER

MJ-1.4 / 1.8 ST H
Low pressure

For versatile crushing



MERICRUSHER

MERICRUSHER

MJ-1.4 / 1.8 ST H Low pressure

For versatile crushing

MERICRUSHER WORKING ENVIRONMENTS

GARDENING

- Crushing of small stumps and branches
- Clearing of vegetation and undergrowth
- Clearing land before seeding and planting

CONSTRUCTION / PROPERTY MAINTENANCE

- Clearing of building sites
- Crushing of small stumps and branches
- Removal of ice and hard packed snow from parking areas, inter sections and sidewalk.

EQUIPMENT

FEATURES

- Bolt mounted counter blades
- Hardox liner (frame MJ-1.8)
- STD Rotor with carbide cutters
- Possibility to turn the direction of the rotor

OPTIONS

- Push bar (fixed)
- Guide plate (front fixed)
- Hardox liner (frame MJ-1.4)

Base machine demand

Compact loaders (skid steer)

Mounting SAE J2513 / Avant

Hydraulic Low pressure (case drain)

Power range 200-250bar 80-170 l/min
2900 / 3600psi 21 / 45 gal/min

Lifting capacity Min 1100kg / 2900 lbs

Technical data:

Transmission Hydraulic

Hydraulic motor Low pressure - gerotor motor

Final transmission Chain 2-row

Rotor diameter 400 mm 20 inch

Rotor width 1.4 / 1.8 1350 / 1750mm 53 / 69 inch

Cutter qty. 1.4 / 1.8 60 / 76 (T25 rotor)

Working depth 200mm / 8 inch

Main dimensions:

Length 815 mm 32 inch

Width 1.4 / 1.8 1580 / 1980 mm 62 / 78 inch

Height 790 mm 31 inch

Weight 1.4 / 1.8 540 / 650 kg 1450 / 1740 lbs

Weight, with options 1.4 / 1.8 750 / 950 kg 2000 / 2550 lbs



SUOKONE OY
88610 Vuokatti
FINLAND

tel. +358 8 666 2011
suokone@suokone.com
www.mericrusher.com