

MERICRUSHER

MJS-160 STG H

For versatile crushing

MERICRUSHER WORKING ENVIRONMENTS

FOREST

- Crushing of leftovers
- Preparing of hauling lines
- Soil preparing for planting
- Maintenance of forest roads
- Clearing of vegetation and undergrowth

AGRICULTURE

- Clearing of farm land
- Farm road maintenance

EQUIPMENT

FEATURES

- Bolt mounted counter blades
- Bolt mounted hardox liner (frame)
- Heavy duty hardox frame
- UNT Rotor with carbide cutters
- Possibility to turn the direction of the rotor

CONSTRUCTION

- Clearing of building sites
- Crushing of stumps
- Ice crushing
- Clearing land before seeding and planting

OPTIONS

- Push bar (fixed 3-positions)
- Rear roller (hydraulic)
- Guide plate (front fixed 3-positions)

Base machine demand

Compact loaders (skid steer)

Mounting SAE J2513

Hydraulic High flow (case drain)

Power range 220-450bar 120-200 l/min

Lifting capacity Min 1800kg / 4000 lbs

Hydraulic motor control 12 V

Technical data:

Transmission Hydraulic

Hydraulic motor High pressure - dual speed

Planetarygear Brevini EM-1045

Final transmission Gear (G-serie)

Rotor diameter / width 500 / 1610mm 20 / 63 inch

Cutter qty. 72

Working depth 250 mm / 10 inch

Main dimensions:

Length 1000 mm 39 inch

Width 1610 mm 63 inch

Height 1050 mm 41 inch

Weight 1350 kg 2980 lbs

Weight, with options 1750 kg 3860 lbs



SUOKONE OY
88610 Vuokatti
FINLAND

tel. +358 8 666 2011
suokone@suokone.com
www.mericrusher.com